



SHELL SIZE	Dim A±0.20	Dim B±0.25	Dim C±0.38	Dim D
09 pin	16.92	24.99	30.80	11.08
15 pin	25.25	33.32	39.10	19.39
25 pin	38.96	47.04	53.00	33.24
37 pin	55.42	63.50	69.32	49.86

MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0) BLACK.
 CONTACT MATERIAL : BRASS.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL FINISH : STEEL NICKEL PLATED.
SPECIFICATION:
 CURRENT RATING : 5 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15MΩ MAX. 10 SES.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

SERIES NO: 10 4-XX 1 X 4 A XX 04
 PRODUCT KIND
 PIN NUMBER
 MALE
 NUT TYPE: 1=NO LOCK NUT
 2=LOCK NUT; 3=ADD NUT

SERIAL NUMBER
 COLOR CODE:
 01:WHITE;05.BLUE
 PLATING CODE:
 A=1u' B=3u'
 DIP HIGH: 4=8.08mm

-TOLERANCES-		GC ELECTRONIC CO.LTD.				
UNLESS OTHERWISE SPECIFIED				TITLE: HDR 公頭鐵殼鍍銀		
X.X ±0.30	X.X° ±3°	APPD:	PRODUCT NO:			
X.XX ±0.15	X.XX° ±1°	CHECK:	DATE	SCALE	UNIT	TYPE
X.XXX ±0.10	X.XXX° ±0.5°	DRAW:	2006.05.13	FREE	MM	Z
						1