



NOTE
 MATERIAL
 INSULATOR: PBT +30%GF
 CONTACTS: BRASS
 SHELL: SPCD
 CONTACT PLATING: GOLD PLATING OVER NICKEL
 ELECTRICAL SPECIFICATION
 CURRENT RATING: 2A;
 CONTACT RESISTANCE: 30mΩ MAX.
 INSULATION RESISTANCE:1000MΩ MIN 500V DC.
 DIELECTRIC WITHSTANDING VOLTAGE:500V AC
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~105°C.

PART NO. DESCRIPTION:
 10 1-XX 1 X 0 X XX 01
 SERIES NO: _____ SERIAL NUMBER
 PRODUCT KIND _____ COLOR CODE:01=WHITE
 PIN NUMBER _____ 02=BLACK 05=BLUE
 MALE _____ PLATING CODE:
 A=1u';B=3u'
 NUT TYPE:1=NO LOCK NUT
 2=LOCK NUT,3=ADD NUT
 _____ USELESS

50M	52.81	61.12	66.93	1.0	55.32	11.0	5.84	3.3
37M	55.42	63.50	69.32	1.0	57.71	11.0	5.84	3.3
25M	38.96	47.04	53.04	1.0	41.43	11.0	5.84	3.3
23M	35.92	44.28	50.56	1.0	38.38	11.0	5.84	3.3
19M	30.75	38.94	44.94	1.0	32.86	11.0	5.84	3.3
15M	25.25	33.32	39.14	1.0	27.51	11.0	5.97	3.3
09M	16.92	24.99	30.81	1.0	19.28	11.0	5.97	3.3
PIN NO:	A±0.20	B±0.10	C±0.20	D±0.20	E±0.20	F±0.20	G±0.20	H±0.20

-TOLERANCES-		GC ELECTRONIC CO.,LTD.				
UNLESS OTHERWISE SPECIFIED		 	TITLE: D-SUB SOLDER MALE			
X.X ±0.30	X.X' ±3°	APPD:	PRODUCT NO:			
X.XX ±0.20	X.XX' ±1°	CHECK:	DATE	SCALE	UNIT	PAGE
X.XXX ±0.10	X.XXX' ±0.5°	DRAW:	2005.09.30	FREE	MM	Z 1