



NOTE

MATERIAL  
 INSULATOR: PBT+30% GLASS FIBER (UL 94V-0) BLACK.  
 CONTACTS: BRASS  
 SHELL: SPCD  
 CONTACT PLATING: GOLD PLATING OVER NICKEL  
 ELECTRICAL SPECIFICATION  
 CURRENT RATING: 5A;  
 CONTACT RESISTANCE: 25mΩ MAX.  
 INSULATION RESISTANCE: 1000MΩ MIN 500V DC.  
 ENVIRONMENTAL  
 OPERATING TEMPERATURE: -55°C~105°C.  
 PART NO. DESCRIPTION:

SERIES NO: 10 5 - XX 2 1 0 0 02 01  
 PRODUCT KIND  
 PIN NUMBER  
 FEMALE  
 NUT TYPE: 1=NO LOCK NUT  
 2=LOCK NUT, 3=ADD NUT

SERIAL NUMBER  
 COLOR CODE: 01=WHITE  
 02=BLACK 05=BLUE  
 PLATING CODE: A=1u'  
 B=3u'  
 USELESS

Shell Size	A±0.20	B±0.25	C±0.38	D±0.20
9	16.33	24.99	30.80	19.14
15	24.66	33.32	39.10	27.47
25	38.38	47.04	53.00	41.19
37	54.84	63.50	69.32	57.65
50	52.20	61.00	67.00	55.01

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表		GC ELECTRONIC CO.,LTD.					
X.X ±0.25	X.X' ±3°	 APPD: 核准:	TITLE: 產品名稱: D-SUB FEMALE CRIMP TYPE				
X.XX ±0.15	X.XX' ±1°		PRODUCT NO: 產品編號:				
X.XXX ±0.05	X.XXX' ±0.5°		DRAW: 繪圖:	DATE	SCALE	UNIT	TYPE
				FREE	MM	Y	1